

## HL7404H, HL7408H, HL7416H

DVR IBRIDO

DVR ibrido a 16,8,4 canali, H.264, 960H, D1 e IP



**HL7404H:** 4 canali full 960H  
**HL7408H:** 8 canali full 960H  
**HL7416H:** 16 canali full 960H  
**H.264**




### CARATTERISTICHE

- ▲ H.264 High profile compression algorithm ideal for standalone DVR
- ▲ Realtime live display up to 24/32 cameras
- ▲ Pentaplex function:live,recording,playback,backup & remote access
- ▲ Support Dual-Streams,to make mobile monitoring very easy,flexible for network transmission
- ▲ Support IE、 Chrome、 Firefox、 Safari browsers
- ▲ Smart video detection:motion detection,video blind,video loss
- ▲ Easy backup methods:USB devices,remote network and client software backup
- ▲ Alarm triggering screen tips,buzzer,e-mail & FTP upload
- ▲ Enable strong multi-way synchronization with max 9/16 channels playback,realize the zero-delay between playback channels
- ▲ Support intelligent video analysis system(IVS),like perimeter detection,items care,flowmeter,abnormal video signal diagnosis
- ▲ DVR,NVR and HVR,3 in 1
- ▲ Support XM Cloud(www.xmeye.net),no need to do router mapping(port forwarding),just 1 step go to internet
- ▲ Support 26 kinds of languages,Arabic,Czech,English,Finnish,Greek,Indonesian,Italian,Japanese,Portuguese,Russian, Thai,T-Chinese,S-Chinese,Turkish,Brazilian,Bulgarian,Farsi,French,German,Hebrew,Hungarian,Polish,Romanian, Spanish,Swedish,Vietnamese

### VISTA POSTERIORE

HL7404H



HL7408H



HL7416H



SPECIFICHE TECNICHE

Model	HL7404H	HL7408H	HL7416H
<b>System</b>			
Main Processor	1*Hi3520A	1*Hi3521	1*Hi3531
Operating System	Embedded LINUX		
System Resources	Pentaplex function:live,recording,playback,backup&remote access		
<b>Interface</b>			
User Interface	GUI,on-screen menu tips		
Preview	1/4	1/4/8/9	1/4/8/9/16
<b>Video</b>			
Video Standards	PAL 625 line,50f/s;NTSC 525 line,60f/s		
Video Compression	H.264 High Profile		
Display Quality	TV:D1,VGA&HDMI: high definition(Max 1920*1080)		
Playback Quality	1080P/720P/960H/D1/HD1/CIF/QCIF		
Encode Capacity	100/120fps 960H	200/240fps 960H	400/480fps 960H
Dec ode Capacity	100/120fps 960H	100/120fps 960H	200/240fps 960H
Hybrid Mode	Only Analog(DVR):4 *960H Analog+IP(HVR):2 *D1+(1*1080P+1*720P) Only IP(NVR):9*D1/8*960H/4*720P /2*1080P /1*720P+7*D1/1*1080P+1*720P+2*D1	Only Analog(DVR):8 *960H Analog+IP(HVR):4*D1+(1*1080P+ 3*720P) Only IP(NVR):16*D1/2*1080P+2*720P /1*1080P+1*720P+6*960H/8*720P	Only Analog(DVR):16*960H Analog+IP(HVR):8*D1+16*D1-/8*D1+8*720P /8*D1+(2*1080P+2 *720P)/4*D1+20*D1/4*D1- (2 *1080P+10*D1)/ 4*D1+(1*1080P+7*720P) /4*D1+(1*1080P+1*720P+10* 960H) Only IP(NVR):24*D1/20*960H/4*1080P /1*1080P+8*720P/2*1080P+4*720P+4*960H
Motion Detect	Zones:192(16*12)detection zones,sensitivity:1-6(6 is highest),Trigger recording,tour,alarm,e-mail&FTP		
<b>Audio</b>			
Audio Compression	G711A		
Bidirectional Talk	Support		
<b>Record &amp; Playback</b>			
Record Mode	Manual>Alarm>Video Detection>Continuous		
Local Playback	1-9channels	1-16channels	1-16channels
Search Mode	Time/Date,Alarm,Motion Detection&exact search(accurate to second)		
<b>Storage &amp; Backup</b>			
Space Occupation	Video: 1080P 80G/day/ch,720P 26G/day/ch,960H 24G/day/ch,D1 16~20G/day/ch; Audio:691.2M/day/channel		
Record Storage	HDD & Network		
Backup Mode	Network download,USB movable HDD,USB DVD-RW,SATA DVR-RW		
<b>Interface</b>			
Video Input	4channel	8channel	16channel
Video Output	2ch BNC,1ch VGA,1ch HDMI	2ch BNC(include 1ch spot),1ch VGA,1ch HDMI	
Audio Input	4channel	8channel	16channel
Audio Output	1channel		
Alarm Input	16channel		
Alarm Output	4channel		
Net Interface	RJ-45(10M/100M)		
PTZ Control	1 RS485, 1 RS232		
USB	2*USB2.0 ports		
HDD	4 SATA ports(Max 4X3T)		
3G/WIFI	Support		
<b>Others</b>			
Power Supply	12V/6A		
Dimension	440mm* 345mm* 60mm		