

LRN3040

4CH POE
NETWORK VIDEO RECORDER




FEATURES

- HD 4channel real-time Recording
- 4channel PoE Support
- Up to 5 Mega-pixel Support
- Small File Sizes by H.264 Compression
- Automatic Network Camera Connection
- HDMI / VGA Video Output
- Two-way Audio Support
- Quick and Easy Archiving using e-SATA
- Automatic Schedule Backup

REAR VIEW



DIMENSION(MM)



VIDEO LRN3040N

Video Input	IP Camera	4Ch/720p Max. Resolution - Up to 5 mega-pixel
Video Output	VGA	1
	HDMI	1

AUDIO

Input	1
Output	1 (Live/Playback, Two-way audio)

ALARM

Input	4
Output	2
Notification to remote PC	Yes

RECORDING

Frame Rate(/sec)	120 FPS @ up to 1280x720
Recording Mode	Continuous, Instant, Event

SEARCH

Playback Function	4 Steps(1x~16x), Forward/Backward
Search Mode	Calendar, Date/Time, Event(Motion,Alarm), Bookmark, Instant

DISPLAY

Resolution	1024x768, 1280x720, 1280x1024, 1920x1080
Division Mode	1, 4

STORAGE

Internal HDD	Interface Type	SATA
	Max. Capacity	1 HDD(up to 3TB)
External HDD	Interface Type	1 x e-SATA, 2 x USB

BACKUP

Backup Interface	USB 2.0, Network, e-SATA
Supportable Device	USB Memory Stick, USB 2.0 HDD, e-SATA HDD

SERIAL I/F

RS-485	1ea(For keyboard controller)
--------	------------------------------

NETWORK

Network Connection	1GbE RJ45 x 1(for external network) 10/100BASE-T RJ45 x 4(PoE+) (for IP camera input)
NTP(Network Time Protocol)	Yes
Bandwidth Control	Yes

SECURITY

User Level Management	Yes
Data Integrity Check(Watermark)	Yes

GENERAL

Power Supply	AC Free 100~240V, 50/60Hz
Operating Temperature	0 - 40 °C
Net Weight(w/o HDD)	1.5kg
Dimension(W x D x H)	264 x 240 x 44mm